

LSV 5-225 Comfort (600136000) Long-neck Sander (220-240 V / 50 - 60 Hz); Plastic Carry Case; with Variable Length Adjustment

Order no. 600136000
EAN 4007430282675



Product may differ from Image



- For convenient sanding of primed surfaces on walls or ceilings
- Selectable LED side light to help detect imperfections and serrations and ensure a perfect finish.
- Optimum balance when working, as the centre of gravity of the machine is not at the sanding head
- Variable length adjustment: can be shortened or extended without tools for narrow rooms or high ceiling rooms
- Extendable to a total length of 2.1 m with additional extension (accessory)
- M-Clean technology: Effective extraction through the machine housing for maximum flexibility of the sanding head
- Ideal adaptation of the flexible sanding head to the surface for good work results
- Optimum extraction results thanks to spring-mounted brush rim that adapts to the surface.
- Vario-Constamatic (VC)-Full wave electronics for working at customised speeds to suit the application materials, and speeds that remain almost constant even under load
- Ergonomically shaped aluminium handle bar and T-handle for comfortable use in different positions
- Simple, quick and tool-free exchangeable shaft can be adjusted directly on site if needed
- Putting the machine down without kinking the hose and cable
- With extensive range of grinding media for every application
- Extraction possibility by means of connecting an all-purpose vacuum cleaner

Technical data

Characteristics

Sanding disc diameter	225 mm / 8 7/8 "
No-load speed	1000 - 1650 rpm
Rated input power	500 W
Output power	270 W
Adjustable machine length	1.1 / 1.6 / 2.1 m // 41 3/8 / 61 7/32 / 81 1/16 "
Weight (without power cable)	4.5 kg / 9.9 lbs
Cable length	4 m / 157 1/2 "

Vibration

Surface grinding	2.5 m/s ²
Uncertainty of measurement K	1.5 m/s ²

Noise emission

Sound pressure level	76 dB(A)
Sound power level (LwA)	87 dB(A)
Uncertainty of measurement K	3 dB(A)

Scope of delivery

- Sanding pad (very soft)
- Coupling bush
- Extension
- Hexagonal wrench
- Plastic carry case
- Hook and loop sanding sheets with multi-perforation (1 each of P80, P100, P120, P150)
- Flexible shaft (as replacement)