

T162 - 5T1.164.103



Welding power source **MMA inverter** – 1Ph 160A

APPLICATIONS

Building Sites, Medium-Light carpentry, Maintenance, Repair, Assembly, Building, Craft, Industry, Hydraulic, petrolchemical industry, agriculture.

MATERIALS

Non-alloy steel, Low-alloy steel, Alloy steel, Stainless steel, Cast iron, Aluminium alloys

FUNCTION

Hot Start, Arc force, Anti sticking.

FOCUS

Accessories included.

**Data
Sheet**

Data Sheet

Supply voltage	1x230 V
Output range	5 A - 160 A
Duty Cycle	35% - A
	60% 160 A
	100% 130 A
Open circuit voltage	80 V
Frequency	50 Hz - 60 Hz
Mains fuses (delayed action)	16 A
Max. connected power	4.9 KvA
Recommended generator rating	5.9 KvA

Data Sheet

Cos j	0.7
Protection classification	IP 23 s
Insulation class	H
Dinse	25 mm ²
Weight	4.6 Kg
Dimensions (WxLxH)	130x330x200 mm
Electrode	Ø mm 1.5 - 4.0
	Cell. Ø mm -

Functions

Hot Start	•
	Data Sheet
Arc Force	•
Anti Sticking	•

