Special floor jacks



Series WWH - Special floor jacks Pneumatic-hydraulic workshop jacks

- Controlled, safe lifting and lowering
- For operation with compressed air from an external source
- Hard chrome-plated piston with extra-smooth surface
- Compact design



WWH 40000 PH incl. 2 extensions 75 mm and 45 mm (can also be plugged into one another)



100 mm extension

New



75 mm height

Model	WWH 40001 PH	WWH 40000 PH	WWH 60000 PH
Article no.	6201140	6201107	6201112
Technical Data			
Load-bearing capacity (lower lifting height)	40 t	40 t	60 t
Load-bearing capacity (medium lifting height)		-	40 t
Load-bearing capacity (top lifting height)	20 t	20 t	20 t
Max. lifting height with 20 t	310 mm	447 mm	312 mm
Max. lifting height with 40 t	245 mm	336 mm	256 mm
Max. lifting height with 60 t	-	-	207 mm
Height of top sections	100 mm	75 + 45 mm	75 + 45 mm
Ground clearance	170 mm	210 mm	150 mm
Weight	51 kg	56 kg	64 kg
Air pressure required	6 - 10 bar	6 - 10 bar	8 - 12 bar
Equipment/scope of supply	 Cast iron rollers with PU coating 1 cast iron extension 100 mm height 	 Cast iron rollers with PU coating 1 cast iron extension 45 mm height 	 Cast iron rollers with PU coating 1 cast iron extension 45 mm height
		1 cast iron extension	1 cast iron extension

75 mm height



