

Manual metal-cutting circular saws with one and two speeds, and swivelling saw head and vice for mitre cuts

- For steel
- two cutting speeds
- Reduction gear, runs in oil bath for low noise
- automatic diaphragm coolant pump with coolant filter as standard
- moving guard ensures optimum safety while cutting
- Control handle with safety switch

- Low-voltage electrical system, 24 Volt, with emergency off switch, main switch, speed selection switch and overload protection
- machine head swivels through 45° anti-clockwise

- **Equipment as of MKS 250 N:**
- As of MKS 250 swivelling machine head 45° anti-clockwise and 45° clockwise
- Vice swivels through 45° anti-clockwise and 45° clockwise
- Quick release vice with double clamping device guarantees precise and virtually burr-free cutting



MKS 250 N
Standard scope of supply



- MKS 255 N**
- Double vice, swivelling from -45° to +45° with quick release
 - **Scope of supply:**
 - Coolant system
 - Cross-cut fence 500 mm
 - Operating tool
 - Without saw blade
 - without chassis

Model	MKS 250 N	MKS 255 N	MKS 275 N
Art. no.	3620251	3620253	3620275
€ plus VAT	1,170.00	1,265.00	1,445.00
Technical specifications			
Motor output 50 Hz	0.9 kW / 230 V	0.95/1.32 kW / 400 V	1.1/1.5 kW / 400 V
Speeds	40 rpm	40/80 rpm	40/80 rpm
Vice jaw width	100 mm	100 mm	105 mm
Saw blade diameter	Ø 250 mm	Ø 250 mm	Ø 275 mm
Run-in height incl. chassis	970 mm	970 mm	970 mm
Dimensions (L x W x H) in mm	800 x 830 x 755	800 x 830 x 755	830 x 900 x 1025
Weight	83 kg	83 kg	98 kg

Cutting capacity MKS 250 N / MKS 255 N

	●	○	□	▭
90°	40	70	70 x 70	55 x 95
45°	35	65	55 x 55	50 x 60
45° +	35	65	55 x 55	50 x 60

Cutting capacity MKS 275 N

	●	○	□	▭
90°	45	65	65 x 65	85 x 60
45°	40	60	40 x 40	40 x 60
45° +	40	60	40 x 40	40 x 60

Cutting capacity MKS 275 N optionally with saw blade 315 N

	●	○	□	▭
90°	45	80	80 x 80	100 x 70
45°	40	80	70 x 70	80 x 70
45° +	40	80	70 x 70	80 x 70