

## SBE 650 (600671510) Impact Drill

(220-240 V / 50 - 60 Hz); Plastic Carry Case

- Vario (V)-electronics for working at customised speeds to suit various application materials.
- Thumbwheel for Speed Preselection
- Clockwise and Anti-clockwise Rotation
- Spindle with hexagonal recess for screwdriver bits for working without chuck

### [Link to Product](#)

#### Illustration



Product may differ from Image

#### Characteristics

Rated Input Power	650 W
Output Power	320 W
Maximum torque	9 Nm / 80 in-lbs
Drill-Ø concrete	16 mm / 5/8 "
Drill Ø steel	13 mm / 1/2 "
Drill-Ø soft wood	30 mm / 1 3/16 "
No-Load Speed	0 - 2800 /min
Revolutions at Rated Load	1500 rpm
Maximum impact rate	44800 bpm
Gears	1
Chuck Capacity	1.5 - 13 mm // 1/16 - 1/2 "
Collar Diameter	43 mm / 1 11/16 "
Drill spindle with hexagonal recess	6.35 mm / 1/4 "

Drill Spindle Thread	1/2 " - 20 UNF
Drill chuck clamping type	Quick-action Keyless Chuck
Weight (without power cable)	1.8 kg / 3.97 lbs
Cable Length	2.55 m / 8.37 ft

#### Vibration

Drilling in metal	5.8 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Impact drilling concrete	24.4 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>

#### Noise emission

Sound Pressure Level	91 dB(A)
Sound power level (LwA)	102 dB(A)
Uncertainty of measurement K	3 dB(A)